



# V7 Portable Security Cable with Combination Lock

SLC4000-13EB

## Key Features

- 2 meter, cut-resistant, galvanized steel cable with vinyl jacket
- 4-resettable digits - allows up to 10,000 combinations
- 90 degree pivot lock head - simple locking in tight spaces
- Rotating, swivel lock housing - easy to see combination
- Compatible with practically all security lock slots

## Overview


The V7 combination security lock is designed for technology products that have a security lock slot and fits practically all notebook computers manufactured today. The security lock provides a simple and effective way to secure notebooks, desktops, monitors and projectors. The push-to-lock function and 90 degree cable design insures easy operation. The lock head tumbler swivels and rotates making it easy to read the numbers when setting the up to 10,000 unique combinations.

## Specification

<b>V7 Model #</b>	SLC4000-13EB
<b>IM SKU #</b>	
<b>EAN</b>	662919049992
<b>Cable diameter</b>	0.17 in / 4.4 mm
<b>Cable length</b>	6.5 ft / 2 meters
<b>Compatibility</b>	Most products having security locks slots
<b>Compliance</b>	RoHS
<b>Country of Origin</b>	Taiwan
<b>Lockhead dimension</b>	0.59 x 1.9 in / 15 x 48.5mm
<b>Material</b>	Zinc alloy
<b>Package Contents</b>	Security lock, 3 secure spacer,1 Velcro strap, user manual and warranty insert
<b>Package dim. (L/W/H)</b>	155 x 38 x 197 mm
<b>Package Includes</b>	Security lock, 3 secure spacer,1 Velcro strap, user manual and warranty insert
<b>Package Weight</b>	200 g
<b>Packaging type</b>	Retail Blister
<b>Product Weight</b>	0.15 kg
<b>Security cable</b>	Galvanized twisted steel wire with vinyl jacket
<b>Warranty</b>	2 years



SLC4000-13EB



The data in this publication is for illustration purposes only and does not necessarily represent standards or specifications which must be met by V7. Design and specifications are subject to change without prior notice. Trademarks belong to their respective owners. No responsibility assumed and all liability for damages resulting from use of this information or for any errors or omissions, are disclaimed. Measurement standards and testing conditions, as per manufacturer definitions, are available on request.