HP LaserJet Enterprise M609 series



The pinnacle of performance and security.

This HP LaserJet Printer with JetIntelligence combines exceptional performance and energy efficiency with professional-quality documents right when you need them – all while protecting your network from attacks with the industry's deepest security



HP LaserJet Enterprise M609dn



HP LaserJet Enterprise M609x









The world's most secure printing

- With HP Sure Start, each printer regularly checks its operating code and repairs itself from attempted hacks.
- Whitelisting checks firmware during startup to help ensure it's authentic, good code digitally signed by HP.
- Run-time intrusion detection continually monitors activity to detect and stop attacks, then automatically reboots.
- Centralise control of your printing environment with HP Web Jetadmin and help build business efficiency.2

High-speed performance meets energy efficiency

- Speed through tasks and save paper. Print two-sided documents nearly as fast as one-sided.
- This printer wakes up fast and prints your first page faster in as quickly as 7.9 seconds.3
- This printer uses exceptionally low amounts of energy thanks to its innovative design and toner technology.4

More. Pages, Performance, and Protection.5

- Produce sharp text, bold blacks, and crisp graphics with precision black toner.
- Original HP Toner cartridges with JetIntelligence deliver more pages per cartridge than predecessors.5
- Help retain the Original HP quality you paid for with anti-fraud and cartridge authentication technology.
- Spend less time replacing toner, and more on business. Choose high-yield toner cartridges.6

Product walkaround

HP LaserJet Enterprise M609x shown

- 1. Hardware Integration Pocket
- 2. 10.9 cm colour touchscreen control panel
- 3. Easy-access USB port
- 4. 100-sheet multipurpose tray 1
- 5. Front door access to toner cartridges
- 6. 550-sheet input tray 2
- 7. 550-sheet input tray 3
- 8. 500-sheet output bin
- 9. Automatic two-sided printing
- 10. Wi-Fi Direct/Bluetooth Low Energy
- 11. Host USB port
- 12. Gigabit Ethernet network port
- 13. Hi-Speed USB 2.0 printing port
- 14. Slot for cable-type security lock





Series at a glance





Model	HP LaserJet Enterprise M609dn	HP LaserJet Enterprise M609x
Product number	K0Q21A	KOQ22A
Print speeds (A4)*	Up to 71 ppm	Up to 71 ppm
Control panel	6.9 cm LCD with keypad	10.9 cm colour touchscreen
Automatic two-sided printing	Yes	Yes
Hardware Integration Pocket**	Yes	Yes
100-sheet tray 1, 550-sheet tray 2	Yes	Yes
550-sheet paper feeder***	Optional (up to four)	Yes (plus up to three optional)
2.100-sheet paper feeder***	Optional	Optional
Envelope feeder	Optional (up to two)	Optional (up to two)
Printer stand	Optional	Optional
5-bin stapler/stacker/mailbox with job offset	Optional	Optional
Direct mobile printing****	Optional wireless direct/NFC	Embedded Wi-Fi Direct/Bluetooth Low Energy
Wireless networking*****	Optional	Optional
HP High-Performance Secure Hard Disk	Optional	Optional

^{*}Measured using ISO/IEC 24734; excludes first set of test documents. For more information, see hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, drive and document complexity.

** Solutions deployed through the Hardware Integration Pocket (HIP) may require additional purchase.

*** Both models come standard with the 100-sheet multipurpose tray and 550-sheet tray 2. The HP Laser Jet Enterprise M609x model comes with one additional 550-sheet paper feeder standard, and can add up

to three additional optional 550-sheet paper feeders and the optional 2,100-sheet paper feeder. The M609dn model can add up to four additional optional 550-sheet paper feeders and the optional 2,100-sheet

paper feeder.
**** Wi-Fi Direct printing and Touch-to-print capability are embedded in the HP LaserJet Enterprise M609x model. The other models can add wireless direct and Touch-to-print capability with the purchase of the optional HP Jetdirect 3000w NFC/Wireless Direct Accessory. The mobile device needs to be connected directly to the signal of a Wi-Fi Direct® supported MFP or printer prior to printing. Depending on mobile device, an app or driver may also be required. For details, see hp.com/go/mobileprinting. Wi-Fi Direct is a registered trademark of Wi-Fi Alliance®. Also, the mobile device must support Near Field Communication (NFC)-enabled printing. For more information, see hp.com/go/businessmobileprinting. Bluetooth Low Energy is standard only on the HP Laser Jet Enterprise M609x model, and it cannot be added to other models. Bluetooth is a trademark owned by its proprietor and used by HP Inc. under license

^{*****} All models can add wireless networking with the purchase of the optional HP Jetdirect 2900nw Print Server. Wireless performance is dependent on physical environment and distance from access point, and may be limited during active VPN connections.

Accessories, Supplies and Support

Supplies	CF237A HP 37A Black Original LaserJet Toner Cartridge		
	CF237X HP 37X High Yield Black Original LaserJet Toner Cartridge		
	CF237Y HP 37Y Extra High Yield Black Original LaserJet Toner Cartridge		
Accessories	LOH17A HP LaserJet 550-sheet Paper Tray		
	LOH18A HP LaserJet 2100 Sheet Paper Tray		
	LOH19A HP LaserJet Printer Stand		
	LOH20A HP LaserJet Stapler/Stacker/Mailbox		
	LOH21A HP LaserJet Envelope Feeder		
	LOH22A Extension Tray Cover		
Connectivity	J8030A HP Jetdirect 3000w NFC/Wireless Accessory		
	J8031A HP Jetdirect 2900nw Print Server		
Service and support	U9MZ0E HP 3 year Next Business Day Hardware Support with Defective Media Retention for LaserJet Enterprise M609 U9MZ1E HP 4 year Next Business Day Hardware Support with Defective Media Retention for LaserJet Enterprise M609 U9MZ2E HP 5 year Next Business Day Hardware Support with Defective Media Retention for LaserJet Enterprise M609 U9NB4PE HP 1 year Post Warranty Next Business Day Hardware Support with Defective Media Retention for LaserJet Enterprise M609 U9NB5PE HP 2 year Post Warranty Net Business Day Hardware Support with Defective Media Retention for LaserJet Enterprise M609		

Technical specifications

Model	HP LaserJet Enterprise M609dn	HP LaserJet Enterprise M609x	
Product number	K0Q21A	KOQ22A	
Functions	Print		
Control panel	Rotating 6.86 cm (2.7 in) QVGA LCD (colour graphics) with 24 key pad.	10.92 cm (4.3 in) Colour Graphics Display (CGD) with touchscreen, rotating (adjustable angle) display, home button	
Print			
Print technology	Laser		
Print speed ¹	Black (A4, normal): Up to 71 ppm; Black (A4, duplex): Up to 58 ppm		
First page out ²	Black (A4, ready): As fast as 5.4 sec; Black (A4, sleep): As fast as 7.9 sec		
Print resolution	Black (best): Up to 1200 x 1200 dpi; Technology: FastRes 1200; 1200 x 1200 dpi		
Monthly duty cycle	Up to 300,000 pages (A4); Recommended monthly page volume: 5,000 to 30,000		
Printer smart software features	Print preview, duplex printing, print multiple pages per sheet (2, 4, 6, 9, 16), collation, watermarks, store print jobs, easy-access USB		
Standard print languages	HP PCL 6, HP PCL 5 (HP PCL 5 driver available from the Web only), HP postscript level 3 emulation, native PDF printing (v 1.7), Apple AirPrint™		
Fonts and typefaces	105 internal TrueType fonts scalable in HP PCL, 92 internal scalable fonts in HP postscript level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale Mono WorldType); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria); Additional font solutions available via third-party flash memory cards; HP LaserJet Fonts and IPDS Emulation available at http://www.hp.com/go/laserjetfonts		
Print area	Print margins: Top: 4.3 mm, Bottom: 4.3 mm, Left: 4.3 mm, Right: 4.3 mm		
Duplex printing	Automatic (standard)		
Processor speed	1.2 GHz		
Connectivity			
Standard	1 Hi-Speed USB 2.0 Device; 2 Hi-Speed USB 2.0 Host; 1 Gigabit Ethernet 10/100/1000T network	1 Hi-Speed Device USB 2.0; 2 Hi-Speed USB 2.0 Host; 1 Gigabit/Fast Ethernet 10/100/1000 Base-TX network; Hardware Integration Pocket; 1 Wi-Fi direct 802.11b/g/n; 1 Bluetooth low energy I/0	
Optional	HP Jetdirect 2900nw Print Server J8031A; HP Jetdirect 3000w NFC/Wireless Accessory J8030A		
Mobile printing capability ³	HP ePrint; Apple AirPrint™; Mopria-certified	HP ePrint; Wireless direct printing; Apple AirPrint™; Mopria-certified	
Supported network protocols	Via built-in networking solution: TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Web Services Printing, IPP 2.0, Apple AirPrint™, HP ePrint, FTP Print, Google Cloud Print; DISCOVERY: SLP, Bonjour, Web Services Discovery; IP CONFIG: IPv4 (BootP, DHCP, AutoIP, Manu TFTP Config, ARP-Ping, IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6); Management: SNMPv2/v3, HTTP/HTTPs, Telnet, TFTP Config, FW Download, Syslog; Security: SNMPv3, SSL Cert Management, Firewall, ACL, 802.1x		
Memory	Standard: 512 MB; Maximum : 1.5 GB, MAX memory, when 1GB Accessory	DIMM is installed	
Media handling			
Number of paper trays	Standard: 2; Maximum: Up to 6	Standard: 3; Maximum: Up to 6	
Media types	Paper (plain, light, bond, recycled, heavy, extra heavy, cardstock, pre-printed, pre-punched, colored, rough, heavy rough), monochrome transparency, labels, letterhead, envelope, heavy envelope		
Media size	Custom (metric): Feeder 1: 76 x 127 to 216 x 356 mm; Feeder 2: 99 x 148 to 216 x 356 mm Supported (metric): Feeder 1: A4, A5, A6, RA4, B5 (JIS), B6 (JIS), 10 x 15 cm, Oficio (216 x 340 mm), 16K, envelopes (C5, B5, C6, DL ISO), Postcard (JIS single and double); Feeder 2: A4, A5, A5-R, B5 (JIS), 16K	Custom (metric): Feeder 1: 76 x 127 to 216 x 356 mm; Feeder 2: 99 x 148 to 216 x 356 mm; Feeder 3: 99 x 148 to 216 x 356 mm Supported (metric): Feeder 1: A4, A5, A6, RA4, B5 (JIS), B6 (JIS), 10 x 15 cm, Oficio (216 x 340 mm), 16K, envelopes (C5, B5, C6, DL ISO), Postcard (JIS single and double); Feeder 2: A4, A5, A5-R, B5 (JIS), 16K; feeder 3: A4, A5, A5-R, B5 (JIS), 16K	

Model	HP LaserJet Enterprise M609dn	HP LaserJet Enterprise M609x	
Product number	K0Q21A	K0Q22A	
Media handling	$\begin{tabular}{ll} \bf Standard input: 100-sheet multipurpose feeder, 550-sheet input feeder \\ \bf Standard output: 500 sheet output bin \\ \bf Optional input: 0ptional 1 \times 550-sheet paper feeder, optional 1 \times 550 \\ paper feeder and stand with cabinet, optional 3 \times 550-sheet paper feeder and stand, optional high-capacity paper feeder and stand with 1 \times 550 \\ sheet feeder and 1 \times 2,000-sheet feeder \\ \end{tabular}$	Standard input: 100-sheet multipurpose feeder, 550-sheet input feeder, 550 accessory feeder Standard output: 500 sheet output bin Optional input: Optional 1 x 550-sheet paper feeder, optional 1 x 550 paper feeder and stand with cabinet, optional 3 x 550-sheet paper feeder and stand, optional high-capacity paper feeder and stand with 1 x 550 sheet feeder and 1 x 2,000-sheet feeder	
Media weight	Feeder 1: 60 to 199 g/m ² ; Feeder 2: 60 to 120 g/m ²	Feeder 1: 60 to 199 g/m ² ; Feeder 2, 3: 60 to 120 g/m ²	
Input capacity	Maximum: Up to 4,400 sheets		
Output capacity	Standard: Up to 500 sheets Envelopes: Up to 75 envelopes Transparencies: 200 Maximum: Up to 1,300 sheets		
Compatible operating systems	Android, Linux Boss (5.0), Linux Debian (7.0, 7.1, 7.2, 7.3, 7.4, 7.5, 7.6, 7.7, 7.8, 7.9, 8.0, 8.1, 8.2, 8.3, 8.4, 8.5, 8.6), Linux Fedora (22, 23, 24), Linux Min (17, 17.1, 17.2, 17.3, 18), Linux Red Hat Enterprise (6.0, 7.0), Linux SUSE (13.2, 42.1), Linux Ubuntu (12.04, 14.04, 15.10, 16.04, 16.10), OS macOS 10.12 Sierra, OS X 10.11 El Capitan, OS X 10.10 Yosemite, UNIX, Windows 10 all 32/64-bit editions (excluding RT OS for Tablets), Windows 70 all 32/64-bit editions (Home Basic, Premium, Professional, etc. Windows XP SP3 32-bit editions (XP Home, XP Pro, etc.)		
Compatible network operating systems	Citrix MetaFrame Presentation Server 3.0, Citrix MetaFrame XP Presentation Server (Feature Release 1, 2, and 3), Citrix on Windows Server 2003/2003 R2, Citrix on Windows Server 2008/2008 R2/2008 R2 SP1, Citrix on Windows Server 2012/2012 R2, Citrix Presentation Server 4.0/4.5, Citrix XenApp 5.0 (Plus Feature Pack 2 & 3) for Windows Server 2008 Terminal Services 32/64-bit, Citrix XenApp 6.0/6.5 (for Windows Server 2008 R2 Terminal Services, 32/64-bit), Citrix XenApp 7.5 (for Windows Server 2018 R2 SP1 Terminal Services, 32/64-bit), Citrix XenApp 7.5 (for Windows Server 2012 and 2012 R2 Terminal Services, 64-bit), Citrix XenDesktop 5.6/7.0/7.5 (for Windows Server 2008 R2 SP1 Terminal Services, 32/64-bit), Citrix XenDesktop 5.6/7.0/7.5 (for Windows Server 2008 R2 SP1 Terminal Services, 32/64-bit), Citrix XenDesktop 7.0/7.5 (for Windows Server 2012 and 2012 R2 Terminal Services, 64-bit), Novell NetWare 6.5/SP8 Novell Clients http://www.novell.com/iprint, Novell iPrint Appliance v1.0, Novell Open Enterprise Server 11/SP1, Novell Open Enterprise Server 2 for Linux, Novell Servers http://www.novell.com/iprint, Windows Server 2003/2003 R2 32/64-bit (SP1/SP2) Standard/Enterprise/Datacenter (+ Cluster & Terminal Services), Windows Server 2008 82/64-bit (SP1) Standard/Enterprise (+ Cluster & Terminal Services), Windows Server 2008 R2 64-bit (SP1) Standard/Enterprise (+ Cluster & Terminal Services), Windows Server 2008 R2 64-bit (SP1) Standard/Enterprise (+ Cluster & Terminal Services), Windows Server 2012/2012 R2 64-bit Standard/Foundation/Essentials/Datacenter (+ Cluster & Terminal Services)		
Minimum system requirements	Windows: 2 GB available hard disk space; OS hardware requirements see h Mac: 1.3 GB available hard drive space; Internet; OS hardware requirements		
Software included	HP Connected, HP Device Experience (DXP), HP PCL 6 (XPS) Printer Driver, H http://www.123.HP.com or OS App Source for printer software), online user	P Software Installer/Uninstaller, Mac OS Welcome Screen (Directs users to	
Security management	Identity management: Kerberos authentication; LDAP authentication; 1000 user PIN codes; optional HP and 3rd party advanced authentication solution: (e.g.; badge readers); Network: IPsec/firewall with Certificate; Pre-Shared Key, and Kerberos authentication; Supports WJA-10 IPsec configuration Plug-ir 802.1X authentication (EAP-PEAP; EAP-TLS); SNMPv3; HTTPS; Certificates; Access Control List; Data: Storage Encryption; Encrypted PDF & Email (uses FIPS 140 validated cryptographic libraries from Microsoft); Secure Erase; SSL/TLS (HTTPS); Encrypted Credentials; Device: Security lock slot; USB port disablement; Hardware integration pocket for security solutions; Intrusion Detection with Red Balloon Security Technology - Constant in-device monitoring for attacks; SureStart Secure Boot - BIOS Integrity Checking with self-healing capability; Whitelisting - loads only known good code (DLLs, EXEs,); Security management: Compatible with HP JetAdvantage Security Manager, Device Security Syslog Messages processed and accessible in Arcsight and Splunk SIEMs		
Printer management	HP JetAdvantage Security Manager; HP SNMP Proxy Agent; HP Web JetAdmin Software; HP WS Pro Proxy Agent; Printer Administrator Resource Kit for HP Universal Print Driver		
Dimensions and Weight			
Printer dimensions (W x D x H)	Minimum: 431 x 466 x 380 mm; Maximum: 431 x 1040 x 453 mm	Minimum: 431 x 466 x 505 mm; Maximum: 431 x 1100 x 581 mm	
Package dimensions (W x D x H)	597 x 497 x 539 mm	762 x 593 x 511 mm	
Printer weight	21.6 kg	26.3 kg	
Package weight	27.2 kg	33.80 kg	
Operating environment	Temperature: 15 to 32.5℃; Humidity: 10 to 90% RH		
Storage	Temperature: -20 to 40°C; Humidity: 10 to 80% RH		
Power ⁴	Requirements: 220V - 240V nominal; +/-10% (min 198V, Max 264V); 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz), 6 A; Power supply type: Buil in 220V Power Supply		
Energy savings feature technology	HP Auto-On/Auto-Off Technology; Instant-on Technology		
Certifications	CISPR 22:2008 (International) - Class A, EN 55022:2010 (EU) - Class A, EN 61000-3-2:2006 +A1:2009 +A2:2009, EN 61000-3-3:2008, EN 55024:2010, EMC Directive 2004/108/EC; Other EMC approvals as required by individual countries ENERGY STAR® qualified; Blue Angel; CECP; EPEAT® Silver; EPEAT® Gold (optional)	CISPR 22:2008 (International) - Class A, EN 55022:2010 (EU) - Class A, EN 61000-3-2:2006 +A1:2009 +A2:2009, EN 61000-3-3:2008, EN 55024:2010, EMC Directive 2004/108/EC; Other EMC approvals as required by individual countries ENERGY STAR® qualified; Blue Angel; CECP; EPEAT® Silver	
What's in the box ⁵	HP LaserJet Enterprise M609dn Printer; HP Black Original LaserJet Toner Cartridge (11,000 yield); CD with software drivers and documentation; Documentation (hardware install guide); Power cord	HP LaserJet Enterprise M609x Printer; HP Black Original LaserJet Toner Cartridge (11,000 yield); CD with software drivers and documentation; Documentation (hardware install guide); Power cord	
Warranty	One-year, next-business day, onsite warranty. Warranty and support options vary by product, country and local legal requirements. Go to http://www.hp.com/support to learn about HP award winning service and support options in your region.		

Footnotes

- Based on HP review of 2016 published security features of competitive in-class printers. Only HP offers a combination of security features that can monitor to detect and automatically stop an attack then self-validate software integrity in a reboot. For a list of printers, visit http://www.hp.com/go/PrintersThatProtect. For more information: http://www.hp.com/go/PrintersEurityclaims.

- ² HP Web Jetadmin is available for download at no additional charge at hp.com/go/webjetadmin.

 ³ Measured after 15 min in sleep. Exact speed varies depending on the system configuration, software application, driver, document complexity and time in sleep.

 ⁴ Based on HP testing using the ENERGY STAR® programme's Typical Electricity Consumption (TEC) method or as reported in energystar.gov versus the top three leading competitors as of 8/2015. Actual results may vary. For details see http://www.hp.com/go/Liclaims.
- ⁵ More pages versus predecessor cartridges claim based on page-yield comparison of HP 37X High Yield Black Original LaserJet Toner Cartridges with HP 87X High Yield Black Original LaserJet Toner Cartridges. For more information, see http://www.hp.com/go/learnaboutsupplies. ⁶ HP 37X High Yield Black Original LaserJet Toner Cartridges not included; please purchase separately.
- ⁷ Measured using ISO/IEC 24734, excludes first set of test documents. For more information, see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

Technical specifications disclaimers

- ¹ Measured using ISO/IEC 24734, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.
- ² Measured using ISO/IEC 17629. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

 ³ May require a firmware upgrade to be compatible, download at http://www.hp.com/go/support
- *Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty.

 5 Cartridges included, yields 11,000 black pages based on ISO/IEC 19798 and continuous printing. Actual yields vary considerably based on images printed and other factors. For details see
- http://www.hp.com/go/learnaboutsupplies









http://www.hp.com/uk

The product could differ from the images shown. © Copyright 2017 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

