Eaton MBP3KI

Catalog Number: MBP3KI

Eaton HotSwap MBP maintenance bypass, 3000 VA, IEC, Input: C20, 200-240V, Outlets: (6) C13, (1) C19

Photo is representative

Powering Business Worldwide

General Specifications

| Product Name | Catalog Number |
|-------------------------------|-----------------------|
| Eaton HotSwap MBP maintenance | MBP3KI |
| bypass | EAN 3553340684227 |
| Product Length/Depth | Product Height |
| 76.5 mm | 50 mm |
| Product Width | Product Weight |
| 439 mm | 1.9 kg |
| Warranty | Compliances |
| 2 year | CE Marked |
| Certifications | Model Code |
| CE | Eaton HotSwap MBP IEC |

defaultTaxonomyAttributeLabel

Туре

Hotswap MBP

Form factor

1U

Outlet control

No

Package contents

Maintenance Bypass Cable locking system Connection cable to the UPS Rack-mounting kit User manual

Operating Temperature

0° to 40°C (32° to 104°F)

Mounting direction

Horizontal/vertical

Color

Black

Input connection

C20

VA rating

3000 VA

Input voltage 200-240V

200-240 V

Phase

Single-phase

Outlets

(6) C13, (1) C19

Number of Outputs C13 6

Number of Outputs C19

1

Number of outlets with earth pin

7

Resources

Brochures

Eaton UPS and battery services - EN

Eaton UPS Services Quick Guide - EN

Compliance information

EU declaration of conformity Eaton FlexPDU and Eaton Hot-Swap MBP

SNMP

No

Ethernet interface

No

Serial interface

No

Mass configuration

No

Electrical connection

Socket outlet

Mounting Dimension (metrical)

50

Mounting dimension (standardized) 482.6 mm (19 inch)

Switchable

No

Over voltage category 2

Fitted with:

LED indication Mounting material

Communication

No



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia