

## **HyperDrive** Next

### **HD4001GL**

### 4 Port USB-C Hub

#### Dimensions:

Length x Width x Height (cm) -  $8.5 \times 3.7 \times 1.5 \text{ cm}$ 

Weight (kg) - Approx. 0.051 Kg

**SRP:** £54.99 | €59.99



# **Product Specification – HD4001GL**

Connection to host device	1100.04	Host system OS compatibility	
Connector type	USB-C*	Works with Windows®	•
Connector technology	USB 3.2 Gen 2 (10 Gbps)	Works with MacOS®	•
Graphics Technology	DP Alt Mode	Works with ChromeOS®	•
		Works with iOS®	•***
Host device port compatibility		Works with Android®	•
USB 3	•	Works with Samsung DEX	•
USB4	•	Works With Linux Ubuntu™	
Thunderbolt 3	•		
Thunderbolt 4	•	Device compatibility	
		Windows® Laptop	•
Video ports		Microsoft Surface® Laptop	•
HDMI	1x HDMI 2.0	ChromeBook®	•
Display Port		Apple iMac®	•
VGA		Apple MacBook Pro® / Air® 2016 - 2019	•
Video via High-speed USB / Thunderbolt port		Apple MacBook Pro® / Air® M1 / M2 2020 - 2022	•
Maximum no. of monitor(s)	1	Apple MacBook Pro® / M1 / M2 Pro / Max 2021 -	
Maximum resolution (single monitor)	4K @ 60 Hz**	2023	•
Maximum resolution (multi-monitor)		Apple iPad Pro® 2018 or later	****
HDR via HDMI		Apple iPad Air® 2020 or later	****
TIBIT VIG TIBIVII		Android® Tablet	•
Connection Ports		Android® Smartphone	<u> </u>
USB-A (Power / Max data speed)	1x USB 3.2 Gen2 (10 Gbps)	Allarola Smartphone	•
OSB A (Fower / Max data speed)	1x USB 3.2 Gen2 (10 Gbps)	Other features	
USB-C (Power / Max data speed)	1x USB 3.2 Gen2 (Max. 100 W PD 3.0 /	Other leatures	Yes - with 100% recycled Aluminiun
OSB-C (FOWEL / Max data speed)	10 Gbps)	Construction material	and up to 85% PCR recycled plastics
Thunderbolt 3	10 dbps)	Construction material	where applicable
Thunderbolt 4	<del></del>	USB-C cable to host device	Built in cable to host device
	<del></del>		
RJ45 Ethernet	<del></del>	Warranty	2 years
3.5 mm Audio	<del></del>		
Other audio ports		Content	
Memory cards			HD4001GL HyperDrive NEXT 4 por
		What's in the box	USB-C Hub
Power			User Guide
	•		
USB Power Delivery to host device	<ul> <li>when hub is connected to optional</li> </ul>		
	USB-C PD 3.0 charger	Notes	
	Max. 100 W PD 3.0 / up to 85 W pass	*Full hub data, video and power functionality will require host device with USB-C port cor Gen 2	npatible with DP Alt Mode, Power Delivery PD 3.0 and USB 3.2 Gen 1
Max. PD power / PD pass through to host	through to host device***	**4K 60 Hz video requires host device USB-C port compatible with DP1.4  *** when using optional 100 W USB-C PD 3.0 charger	
	till ought to most acvice	**** Compatible with iPad® with USB-C/ Thunderbolt <sup>TM</sup> port. Using extended mode onto	external monitor requires iPadOS 16 or later
Recommended USB-C chargers			
Hyper HJG100 100 W GaN charger	•		
Hyper HJG140 140 W Universal GaN charger	•		
Targus APA108 100 W laptop charger	•		