



4" Professional label printer solution

TD-4650TNWB / TD-4750TNWB / TD-4650TNWBR /
TD-4750TNWBR Data Sheet



Windows 10

Bluetooth

iOS

CERTIFIED USB

TD-4T Series

The versatile TD-4T desktop printer series uses high capacity thermal transfer ink ribbons for durable labelling and ultimate productivity.

This range of desktop printers offers RFID capabilities for identification, tracking, security and a range of other applications to meet your needs.

Key Features:

- Thermal transfer printing
- Compatible with Windows[®], Mac[®] and Linux
- Mobile operating system support using Software Development Kits (SDKs)
- Additional software including Seagull BarTender driver with Ultra Lite edition (downloadable)
- Fast print speeds of up to 203mm/sec (8ips)
- Various printer command languages supported
- 2.3 inch colour LCD display with 6-button navigation



General

Carton contents	AC adaptor USB cable Documentation 2 x 1" ribbon spindles for 300m ribbon 1" ribbon paper core
Language support	Dansk, Deutsch, English, Español, Français, Italian, Nederlands, Norsk, Português, Suomi, Svenska

Dimensions & Weights

Without carton	219(w) x 284(d) x 191(h) 3.0kg
-----------------------	----------------------------------

Built In Features

Printing Method	Direct Thermal / Thermal Transfer
Print Resolution	TD-4650TNWB / TD-4650TNWBR: 203dpi TD-4750TNWB / TD-4750TNWBR: 300dpi
Print Speed	TD-4650TNWB / TD-4650TNWBR: 203mm/sec TD-4750TNWB / TD-4750TNWBR: 152mm/sec
Print Width	TD-4650TNWB / TD-4650TNWBR: 108mm TD-4750TNWB / TD-4750TNWBR: 105.7mm
Minimum print length	Continuous: 5mm Tear mode: Media width < 2 inch: 25.4 mm Media width ≥ 2 inch: 50 mm Peeler mode: 25.4mm Cutter mode: 25.4mm
Maximum print length	TD-4650TNWB/TD-4650TNWBR: 25400mm TD-4750TNWB/TD-4750TNWBR: 11430mm (Peeler mode: 152.4mm)
Minimum media width	20mm
Maximum media width	112mm
Maximum roll diameter	127mm
Minimum roll core diameter	25.4mm & 38.1mm
Minimum ribbon width	40mm
Maximum ribbon width	110mm
Suggested paper core width	0.5" paper core: fixed width 110mm, width 2 notches in each side 1" paper core: fixed width 110mm with 2 notches in each side 1" paper core: paper core width is the same as ribbon width and use with ribbon spindles
Inner paper core & ribbon length	0.5" paper core: Max. OD 40 mm, 110M long 1" paper core: Max. OD 67 mm, 300M long
RFID Type[^]	UHF
RFID label length[^]	On-pitch 0.625 inch or longer

RFID Inlay[^]	Compatible with EPC global Class 1 Gen2 (ISO 18000-6C) compliant inlays
RFID Antenna[^]	Adjustable to enable support of a wide array of RFID labels
RFID media width[^]	20 – 112mm
RFID media length[^]	16.5mm – max. length
Interfaces	USB Ver.2.0 (Full Speed) (Type B), USB Host Serial RS232C (DB9 female) Wired LAN 10/100BASE-TX Wi-Fi 802.11 a/b/g/n , Bluetooth v4.2
Control Panel	2.3-inch Colour LCD display (incl. Real time clock) 6 button navigation
Printer commands	FBPL-EZD (EPL2,ZPL2,DPL)
Internal fonts & sizes	8 alpha-numeric bitmap fonts for FBPL Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font
Memory	RAM: 128MB Flash: 128MB
Internal Barcode	Linear: Code128UCC, Code128 subsets A, B, C, EAN128, Interleaved 2 of 5, Interleaved 2 of 5 with check digit, Code39, Code39 with check digit, Code93, EAN13, EAN8, UPCA, UPCE, EAN and UPC 2 (5) digits add-on, Codabar, Postnet, MSI, MSI with check digit, PLESSEY, China post, ITF14, Code11, TELEPEN, TELEPENN, PLANET, Code49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS 2-dimensional: GS1 DataBar, GS1 DataMatrix, Maxicode, AZTEC, PDF417, QR Code, Micro PDF 417
Operating system support	Microsoft® Windows® 7 / Windows® 8 / Windows® 8.1 / Windows® 10 Microsoft® Windows® Server 2008 / Server 2008R2 / Server 2012 / Server 2012R2 / Server 2016 OS X 10.10.x,10.11.x macOS 10.12.x,10.13.x,10.14.x 10.15 Ubuntu V11.04-16.04 / Fedora 24 / SUSE Linux Enterprise Server 12 / CentOS Linux 7.2 / Red Hat Enterprise 7.3

Windows SDK	Microsoft® Windows® 7 / Windows® 8 / Windows® 8.1 / Windows® 10 Microsoft® Windows® Server 2008 / Server 2008R2 / Server 2012 / Server 2012R2 / Server 2016 / Server 2019
Mobile SDK	Android v5 – v10 iOS v9 – v13.2 Requires 3 rd party app development using Brother SDK, further information available at www.brother.eu/developer
Software	BarTender Ultra Lite Edition: Barcode label design software Brother Printer Management Tool: Software to centrally manage devices for updating settings, firmware and other configurations. (Microsoft® Windows® 7 / Windows® 8 / Windows® 8.1 / Windows® 10 only), Microsoft® Windows® Server 2012 / Server 2016 / Server 2019)

Environmental

Operating Temperature	5°C to 40°C
Operating Humidity	25% to 85% non-condensing
Storage Temperature	-40°C to 60° C
Storage Humidity	10% to 90% non-condensing

Supplies

Roll type*	Uncoated label: BUS-1J074102-121: 102mm x 74mm, 1100 labels BUS-1J150102-121: 102mm x 150mm, 550 labels Coated label: BCS-1J074102-121: 102mm x 74mm, 1100 labels BCS-1J150102-121: 102mm x 150mm, 550 labels
-------------------	--

Standard Wax:

BWS-1D300-060: 60mm x 300m
BWS-1D300-080: 80mm x 300m
BWS-1D300-110: 110mm x 300m

Premium Wax:

BWP-1D300-060 – 60mm x 300m
BWP-1D300-080 – 80mm x 300m
BWP-1D300-110 – 110mm x 300m

Standard Wax/Resin:

BSS-1D300-060: 60mm x 300m
BSS-1D300-080: 80mm x 300m
BSS-1D300-110: 110mm x 300m

Ribbon type*

Premium Wax/Resin:

BSP-1D300-060: 60mm x 300m
BSP-1D300-080: 80mm x 300m
BSP-1D300-110: 110mm x 300m

Standard Resin:

BRS-1D300-060: 60mm x 300m
BRS-1D300-080: 80mm x 300m
BRS-1D300-110: 110mm x 300m

Premium Resin:

BRP-1D300-060: 60mm x 300m
BRP-1D300-080: 80mm x 300m
BRP-1D300-110: 110mm x 300m

Optional Accessories (Dealer Option)

Label Peeler**	PA-LP-004
Full & Partial Cutter**	PA-CU-003
External Roll Holder (User Option)	PA-RH-001

*For additional supplies information, please contact your local Brother office

**Not recommended for use with RFID tags

^Only supported on TD-4650TNWBR and TD-4750TNWBR

All specifications are correct at the time of printing and are subject to change without notice. Brother and the brother logo are both trademarks of Brother Industries, Ltd., registered in Japan and certain other countries. Any trade names, logos and product names of other companies appearing are trade names or trademarks of those respective companies.

BIE Product Planning: Last updated 26/06/2020