



ISO/IEC 19752 Yield Test Report

Part Number: 64415XA
64435XA

T640, T642, T644 Extra High Yield Print Cartridge
Printer: T644

see below for additional part numbers

Declaration of Yield:	Average Cartridge Yield	32000	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 34296
Std Dev 1163
90% Lower Confidence 33575

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date tested **start** 25-Mar-2005 **stop** 30-Mar-2005

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake At toner low
Print mode	Continuous
Number of printers tested	3
Media used	Boise Cascade - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	T644 version 1
Operating system	Windows 2000
Application software	Acrobat version 6.01
Test page version	Down load Free__19752 Test Chart.pdf

Cartridge testing data:	Cartridge	Printer	Temperature				Humidity			Cartridge Yield	Cartridge used in Calculation		
			Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg			Max	Min
	CAS050559299	PL2-1192-H	74	24	75	24	72	22	46	53	44	33880	Yes
	CAS050559301	PL2-1191-H	74	24	75	24	72	22	46	53	44	33120	Yes
	CAS050559297	PL2-1192-H	74	24	75	24	72	22	46	53	44	33999	Yes
	CAS050559290	PL2-1191-H	74	24	75	24	72	22	46	53	44	35399	Yes
	CAS050559304	PL2-1191-H	74	24	75	24	72	22	46	53	44	33739	Yes
	CAS050559303	PL2-1190-H	74	24	75	24	72	22	46	53	44	35560	Yes
	CAS050559285	PL2-1192-H	74	24	75	24	72	22	46	53	44	35680	Yes
	CAS050559307	PL2-1190-H	74	24	75	24	72	22	46	53	44	34921	Yes
	CAS050559327	PL2-1190-H	74	24	75	24	72	22	46	53	44	32362	Yes

Comments and or exceptions:

also covers:

- 64404XA 64416XE 64436XE
- 64404XE 64417XR 64437XR
- 64404XL 64418XL 64438XL
- 64404XR